MOLD RELEASE 225 BLUE

SDS DATE: 01/01/2021

Section 1: Product Identification

Responsible Party:

Lilly Ram Chemical Products 1740 E. Monticello Ct. Ontario, CA 91761-9998

Tel: 909-223-9699 Fax: 909-923-2226

E: composites@lillyram.com

Emergency Telephone number: Transport North America: Chemtrec 1-800-424-9300

This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

Product ID: 87-08

Product Name: Mold Release 225 BLUE

Intended Use: Paint product

Section 2: Hazard(s) Identification

GHS Classification

Flammable Liquids: Category 3
Skin irritation: Category 2
Eye Irritation: Category 2A
Toxic to Reproduction Category 1B

Specific target organ toxicity- single exposure: Category 1 (Central Nervous System)

Specific target organ toxicity- single exposure: Category 3 (Narcotic effects)

Specific target organ toxicity- repeated exposure: Category 1
Aspiration hazard: Category

GHS Label Elements

Hazard pictograms:





Signal Word: Danger

EMERGENCY OVERVIEW: Appearance: Liquid Color: Clear, colorless Odor: Aromatic Hydrocarbon

Hazard Statements: Flammable liquid and vapor.

Harmful if swallowed and enters airways.

Causes skin irritation

Causes serious eye irritation.

May damage fertility

May damage the unborn child

Causes damage to organs: (central nervous system (CNS), kidneys, liver,

Respiratory tract irritation, Narcotic effects.

May cause drowsiness and dizziness.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion proof electrical, ventilating, and lighting and all material handling equipment.

Use only non-sparking tools

Take precautionary measures against static discharge.

Keep container tightly closed when not in use. Do not breathe fume/ mist/ vapors/ spray

Wash exposed skin areas thoroughly after handling. Wear protective gloves/ eye protection/ face protection.

Response: GENERAL: Get medical attention if you feel unwell. If exposed: Call a Poison Center or physician.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call

a POISON CENTER or a physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth with water. Give one or two glasses of water. Do not induce vomiting unless told to do so by medical personal. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration

IF ON SKIN: Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs get medical advice/attention. Wash contaminated clothing prior to reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If irritation occurs/persists contact a physician.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an approved waste disposal plant.

Potential Health Effects, Carcinogenicity:

IARC	Group 2B: Sufficient animal data	Ethylbenzene	.1 – 1%	100-41-4
ACGIH	Confirmed animal carcinogen with unknown relevance to hum	nans.		
		Ethylbenzene	.1 – 1%	100-41-4
NTP	Some evidence of carcinogenicity in male/female rats of	or mice		
		Ethylbenzene	.1 – 1%	100-41-4
OSHA	Hazard communication carcinogens - present	Ethylbenzene	.1 – 1%	100-41-4

California Prop 65: Ethylebenzene listed. Initial date 6-1-04 carcinogen

Section 3: Product Composition

	CAS#	%Approx. wt.
Solvent Naphtha, petroleum light aliphatic	64742-89-8	55-70
Isopropyl Alcohol	67-63-0	25-30
Xylene	1330-20-7	1 - 5
Ethylbenzene	100-41-4	.0 - 1

Specific chemical identity and exact percentages are withheld as Trade Secret.

Section 4: First-Aid Measures

Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician:

quantities have been ingested or inhaled.

Specific treatments:

Protection of first aid

personnel:

No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

Section 5: Fire-Fighting Measures

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry chemical, foam and/or water fog.

UNSUITABLE EXTINGUISHING MEDIA: Do not use high volume water jet.

No specific treatment.

SPECIFIC HAZARDS DURING FIREFIGHTING: Do not allow run-off from firefighting to enter drains or water courses.

HAZARDOUS COMBUSTION PRODUCTS: Decomposition products may include carbon dioxide and carbon

monoxide. Measurements at temperatures above 150°C in presence

of air have shown that small amounts of formaldehyde are

formed due to oxidative degradation.

SPECIFIC EXTINGUISHING METHODS: Use a water spray to cool fully closed containers.

FURTHER INFORMATION: Collect contaminated fire extinguishing water separately. This must

> not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local

regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Wear self-contained breathing apparatus for firefighting if necessary.

FLASH POINT: 20°F (-7°C)

Section 6: Accidental Release Measures

Personal Precautions, protective equipment Use personal protective equipment.

and emergency procedures:

Ensure adequate ventilation.

Evacuate personnel to safe areas. Remove all sources of ignition.

Be aware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

Use only non-sparking tools.

Environmental Precautions: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective

authorities.

Methods and Materials for containment and cleaning up: (e.g. sand, earth, diatomaceous earth, vermiculite)

Contain spillage, and then collect with noncombustible absorbent material, and place in container for disposal according to local/national regulations (see section13). Keep in suitable, closed containers for disposal.

Section 7: Handling and Storage

Advice on Safe Handling: Avoid formation of aerosol.

Do not breathe vapors.

Avoid exposure- obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national regulations.

Conditions for Safe Storage: Prevent unauthorized access.

No smoking.

Store in a segregated and approved area. Protect from direct sunlight.

Keep container tightly closed in a dry and well ventilated place.

Containers which are opened must be carefully resealed and kept upright to prevent

leakage.

Observe label precautions.

Electrical installations/working materials must comply with the technological safety

standards.

Section 8: Exposure Control / Personal Protection

Components with workplace control parameters

Component	CAS No.	Value type (Form of Exposure)	Permissible Concentration	Basis
Solvent Naphtha, petroleum	6472-89-8	PEL	500 ppm /2,000 mg/m ³	OSHA Z-1
light aliphatic	0472-03-0	TWA	400 ppm	ACGIH
		TWA	400 ppm/1,600 mg/m ³	OSHA Z-1A
Isopropyl Alcohol	67-63-0	TWA	400 ppm	OSHA PEL
		TWA	400 ppm	NIOSH REL
		TWA	200 mg/m ³	ACGIH
		STEL	400 ppm	
Xylene	1330-20-7	TWA	100 ppm	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	
Ethylbenzene	100-41-4	TWA TWA TWA	100 ppm 100 ppm 20 ppm	OSHA PEL NIOSH REL ACGIH

Personal Protective Equipment

Respiratory Protection: If exposure cannot be controlled below applicable limits, use the appropriate NIOSH

approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator

manufacturer's instructions.

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapors from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical / ventilating / lighting /

equipment.

Hand Protection Remarks: The suitability for a specific workplace should be discussed with the producers of

protective gloves.

Eye Protection: Eye wash bottle with pure water.

Tightly fitting safety goggles.

Wear face-shield and protective suit for abnormal processing situations.

Skin and Body Protection: Impervious clothing.

Choose body protection according to the amount and concentration of the dangerous

substance at the work place.

Hygiene Measures: Avoid contact with skin, eyes, and clothing.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling the product.

Section 9: Product Properties

Appearance: Liquid

Color: Clear, colorless
Odor: Aromatic hydrocarbon
Odor threshold: No data available
pH: No data available
Freezing Point: No data Available
Boiling Range: No data Available
Flash Point: 20°F (-7°C)

Evaporation Rate: 2.3 (butyl acetate = 1.0)
Flammability (solid, gas) No data available

Upper explosion limit 12% Lower explosion limit 1%

Vapor pressure 103mm/Hg @ 100°F

Vapor density 3.7 (air = 1.0)

Specific gravity 0.76

Acute Toxicity

Acute dermal toxicity

Water solubility
Solubility in other solvents
Partition Coefficient
Auto Ignition Temperature
VOC Content
Density
Insoluble in water
No data available
No data Available
No data Available
6.33 lbs./gal.

Section 10: Stability and Reactivity

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical Stability: Stable under normal conditions.

 LD_{50} (rat) :> 2,000 mg/kg

Possibility of Hazardous Reactions: Vapors may form explosive mixture with air. Sensitivity to static discharge hazards.

Conditions to Avoid: Keep away from heat, flames, sparks and other ignition sources.

Incompatibility materials: Strong oxidizing agents.

Hazardous Decomposition products: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Section 11: Toxicological Information

LD₅₀ (rabbit):1700 mg/kg

LD₅₀ (rabbit):15354 mg/kg

Skin corrosion/irritation:Irritating to skinNo irritating to skinIrritating to skinIrritating to skinNot classifiedSerious eye damage/Non-irritating to eyes.Irritating to eyesIrritating to eyesNot classified

Serious eye damage/ Non-irritating to eyes. Irritating to eyes Irritating to eyes Not classified 24h exposure time, rabbit,

Respiratory or skin Not a skin sensitizer Not a skin sensitizer No information available Not classified Sensitization

Date of Issue Date of Revision: 01/01/2021 Date of previous Issue: 01/15/2018 Version: 1

LD₅₀ (rabbit):12870 mg/kg

Germ cell mutagenicity No information available No effects in lab animals No effects in lab animals May cause genetic defects Carcinogenicity No information available Not classifiable No effects in lab animals Class mutagen 1B Suspected of causing cancer Reproductive toxicity No information available No teratogenic effects in lab No effects in lab animals Suspected of damaging fertility or the unborn child animals STOT single exposure May cause respiratory Not data available Not data available Not data available irritation. May cause drowsiness or dizziness. STOT repeated exposure Hearing loss (rats) Classified as Category 2 May damage organs to Central nervous system High concentrations of hearing and kidney depression similar Materials has been associated with irregular heart rhythms and cardiac arrest. **Aspiration toxicity** Harmful if swallowed May be harmful if swallowed May be harmful if May be fatal

Section 12: Ecological Information

swallowed

and enters airways

if swallowed

and enters airways

Ecotoxicology assessment

Pseudomonas putida: 1,050 mg/l LD₅₀ (algae) >1 <10mg/l effects.

Chronic aquatic toxicity Toxic to aquatic life with No data available NOEL (Fish)>1 mg/l Long lasting effects

long lasting effects

Readily biodegradable

Mobility in soil

No data available

Adsorbs on soil

No information available

No information available

Other adverse effects

No data available

unlikely to pose a significant hazard to aquatic life.

environment

Product

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA Section 602 Class 1

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S.

Clean Air Act section 602 (40 CFR 82, Subpt. A, App.A + B).

Section 13: Disposal Information

Material Disposal: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity

and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in

drains or in water courses. Waste product should not be allowed to contaminate soil or water.

Container Disposal: Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Refer to

Section 7 before handling

the product or containers. Residues may cause an explosion hazard. Do not puncture, cut or weld

uncleaned drums. Send to drum recoverer or metal reclaimer.

Local Legislation: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied

with.

Section 14: Transportation Information

IATA: UN 1993, Flammable Liquid, N.O.S., (Naphtha, isopropanol), 3, II, (Flash Point: 20°F)
IMDG: UN 1993, Flammable Liquid, N.O.S., (Naphtha, isopropanol), 3, II, (Flash Point: 20°F)
DOT: UN 1993, Flammable Liquid, N.O.S., (Naphtha, isopropanol), 3, II, (Flash Point: 20°F)

Section 15: Regulatory Information

U.S. Federal Regulations:

Ingredient Name (CAS #)	Approx. Weight%		SARA 302	SARA 313	CERCLA RQ. in lbs.
Xylene (1330-20-7)	1 - 5		Form R repor For 1.0% de l Concentration	minimis	100
Ethylbenzene (100-41-4)	0.1 – 1		Form R repor For 1.0% de l Concentration	minimis	100
SARA 311/312 Hazard Class:	Acute: Chronic: Flammability: Reactivity: Sudden pressure:	yes yes yes no no			

U.S.STATE REGULATIONS:

Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under Pennsylvania Code, Chapter 317.

 Xylene
 1330-20-7

 Naphtha
 64742-89-8

 Isopropyl alcohol
 67-63-0

California Proposition 65:

WARNING! This product contains a chemical known in the State of California to cause cancer.

Rule 66 status of product: Not photo chemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

Section 16: Other Information

HMIS ratings Health: 2 Flammability: 3 Physical hazard: 1 PPE: X – see section 8

<u>Disclaimer:</u> The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Lilly-Ram assumes no obligation or liability for use of this information. UNLESS LILLY-RAM AGREES OTHERWISE IN WRITING, LILLY-RAM MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. LILLY-RAM WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This SDS contains additional information required by the state of Pennsylvania.

Preparation Information:

Prepared By: Chase Williams

SDS Prep date to GHS: 01 / Jan / 2021 Previous Issue 15/ Jan / 2018

End of Safety Data Sheet.